













Air Separation Plants

Solutions for highest purity worldwide



For purest applications.

Cryogenic air separation plants have proven themselves and been worth their value throughout the world for many years now. These systems are particularly suitable for the production of liquid and / or gaseous oxygen, nitrogen and argon. The precious products are gained from atmospheric air, based on a low-temperature rectification process. Thereby the substances are of high purity and find wide fields of application in medicine and industry.

CONTACT

CRYOTEC Anlagenbau GmbH

Dresdener Straße 76 04808 Wurzen Germany

GERMANY

Phone: +49 3425 89 65 - 1610 Fax: +49 3425 89 65 - 1638 Email: contact@cryotec.de Web: www.cryotec.de











Air Separation Plants Standard and tailor-made

GASEOUS OXYGEN (GOX), NITROGEN (GN), ARGON (GAR)

Standard and tailor-made plants of models ONG and OANG Standard models: **ONG** 1,000 / 2,000 / 5,000 / 10,000 OANG 1.000 / 2.000 / 5.000 / 10.000

Product Product Output* **Product Purity** GOX 150 - 10,000 Nm³/h 99.5 - 99.7 % by vol. GN 300 - 20,000 Nm³/h up to 1 ppm (v) O₂ GAR 12 - 240 Nm³/h ** up to 5 ppm (v) O₂

During the production of gaseous Oxygen, Nitrogen and Argon, certain amounts of liquid products (LOX, LIN, LAR) can be produced simultaneously.

HIGH PURITY NITROGEN

Standard and tailor-made plants

Standard models: **NG** 300 / 500 / 1,000 / 2,000 / 3,000 5,000 / 7,000 / 10,000 / 15,000

Product Output* Product

Product Purity 300 - 15,000 Nm³/h up to 1 ppm (v) O₂ in N₂

Product Pressure*

6 - 8 bar/g

Certain amounts of liquid nitrogen (LIN) can be produced simultaneously.

LIQUID OXYGEN (LOX), NITROGEN (LIN), ARGON (LAR)

Standard and tailor-made plants of models ONL and OANL Standard models: **ONL** 100 / 200 / 500 / 1,000 / 2,000 / 5,000 OANL 500 / 1.000

Product Output* Product **Product Purity** 99.5 - 99.7 % by vol. LOX 100 - 5,000 Nm³/h LIN 100 - 5,000 Nm³/h up to 1 ppm (v) O₂ LAR 15 - 30 Nm³/h ** up to 5 ppm (v) O₂

CHARACTERISTICS

- Quality and functional check in CRYOTEC workshops (depending on the plant size)
- Very short erection / commissioning time due to ready piped and wired plant skids
- Application of trusted and well-proven equipment
- · Efficient plant operation
- · Competitive solution due to standardization
- High quality by applying a quality management system according to ISO 9001 standard
- * Other product capacities and pressures on request

Additional Equipment

- Pipeline service / compressors, for increasing the production pressure up to the specific requirements of the customer
- · Liquid gas tanks for storage of liquid products
- · Liquid gas pumps, vaporizers
- · Cylinders filling manifolds

Specials

- Automatic process control by PLC guarantees highest plant availability
- Air cooling at ambient temperatures up to +50°C (122°F) possible and water cooling at ambient temperature up to +60°C (140°F)
- · Plants tailored to the specific needs of the customer
- · Full service in all project phases: planning, design, manufacturing, delivery, supervision, commissioning and start-up of the plant
- · Long-term customer service and assistance

High Plant Safety

- High reliability due to high plant safety and long-term experience in process design, plant engineering and construction
- Design according to latest safety standards of the oil and gas industry

HIGHLIGHTS OF LOX/LIN/LAR PLANTS

- Compact design (skid mounted or containerized)
- · Quality and functional check in CRYOTEC's own workshop
- · High efficiency in plant operation
- Very short erection / commissioning time due to prefabricated and tested plant units







Corinne Ziege Managing Director Phone: +49 3425 89 65 - 1610 Email: corinne.ziege@cryotec.de





- Liquefaction of Gases Small Scale LNG Systems
- CO Technologies



- Polymers & Fibers Chemistry & Specialty Chemistry
- Renewable Energies
- Engineering Services & Infrastructure



- Construction Engineering
- Infrastructure
 Building & Civil Engineering
- · Project Management
- Technical Building Equipmen



^{**}Argon production is possible from 500 Nm³/h Oxygen / Nitrogen production

^{**}Argon production is possible from 500 Nm3/h Oxygen / Nitrogen production